

Blackmagic URSA Mini Pro 12K



URSA Mini Pro 12K is a revolution in digital film with a 12,288 x 6480 12K Super 35 sensor and 14 stops of dynamic range. The third generation URSA Mini Pro features new color science and shoots 80 megapixels per frame in Blackmagic RAW. You also get built in ND filters, user changeable lens mount and recording to dual CFast or SD cards. URSA Mini Pro 12K even supports recording direct to a flash disk or SSD using its built in SuperSpeed USB-C connection!

£8,095

Camera Features

Effective Sensor Size

27.03mm x 14.25mm (Super35)

Lens Mount

PL mount included. Interchangeable with optional EF and F lens mounts.

Lens Control

12pin broadcast connector for compatible lenses and electronic control via EF mount pins on optional EF lens mount.

Dynamic Range

14 Stops

Shooting Resolutions

12,288 x 6480 (12K DCI)
 11,520 x 6480 (12K 16:9)
 12,288 x 5112 (12K 2.4:1)
 7680 x 6408 (12K Anamorphic)
 8192 x 4320 (8K DCI)
 7680 x 4320 (8K 16:9)
 8192 x 3408 (8K 2.4:1)
 5120 x 4272 (8K Anamorphic)
 6144 x 3240 (6K Super16)
 4096 x 2160 (4K Super16)
 4096 x 2160 (4K DCI)
 3840 x 2160 (4K 16:9)
 4096 x 1704 (4K 2.4:1)
 2560 x 2136 (4K Anamorphic)

Frame Rates

Maximum sensor frame rate dependent on resolution selected. Project frame rates of 23.98, 24, 25, 29.97, 30, 50, 59.94 and 60 fps supported.

High Speed Frame Rates

12K 17:9 full sensor up to 60 fps
 8K DCI full sensor up to 110 fps
 4K DCI full sensor up to 110 fps
 8K 2.4:1 and 4K 2.4:1 up to 140 fps
 6K Super 16 up to 120 fps
 4K Super 16 up to 220 fps

Built in ND Filters

Four position ND filter wheel with clear, 2-stop, 4-stop and 6-stop IR ND filters.

Focus

Focus button turns on peaking, auto focus available using compatible lenses.

Iris Control

Iris wheel and touchscreen slider for manual iris adjustment on electronically controllable lenses, iris button for instant auto iris settings on compatible lenses so no pixel is clipped in film mode. Scene average auto exposure in video mode.

Screen Dimensions

4 inch

Screen Type

LCD capacitive touchscreen.

Metadata Support

Automatically populated lens data from i/Technology with compatible PL lenses and electronic EF lenses when using optional EF lens mount. Automatic recording of camera settings and slate data such as project, scene number, take and special notes.

Controls

Touchscreen menus on 4 inch screen. Push buttons for other controls. 3 assignable shortcut keys.

Timecode Clock

Highly accurate timecode clock. Less than 1 frame drift every 8 hours.

Connections**Total Video Inputs**

1 x 12G-SDI

Total Video Outputs

1 x 12G-SDI, 1 x 3G-SDI Monitoring.

SDI Rates

1.5G, 3G, 6G, 12G.

Analog Audio Inputs

2 x XLR analog switchable between mic, line and AES audio. Phantom power support.

Analog Audio Outputs

1 x 3.5mm headphone jack, supports iPhone microphone for talkback.

Reference Inputs





Tri-Sync/Black Burst/Timecode.

Remote Control

1 x 2.5mm LANC input for Rec Start/ Stop, plus Iris and Focus control using compatible lenses.

Computer Interface

1 x USB Type-C 3.1 Gen 2 with power delivery for external drive recording. 1 x USB Type-C for software updates.



Audio

Microphone

Integrated stereo microphone.

Built in Speaker

1 x mono speaker.

Standards

SD Video Standards

None.

HD Video Standards

1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p50,
1080p59.94, 1080p60, 1080i50,
1080i59.94, 1080i60

Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25,
2160p29.97, 2160p30, 2160p50,
2160p59.94, 2160p60

SDI Compliance

SMPTE 292M, SMPTE 424 Level B,
SMPTE 2081-1, SMPTE 2082-1

SDI Audio Sampling

48 kHz and 24 bit

Media

Media

2 x CFast 2.0 card slots, 2 x SD UHS-II card slots, 1 x USB-C 3.1 Gen 2 expansion port with power delivery for recording to external media. Please refer to either the Manual or the Information Note at www.blackmagicdesign.com/ support for compatible media.

Media Format

Can format media to ExFAT (Windows/Mac) or HFS+ (Mac) file systems.

Supported Codecs

Codecs

Blackmagic RAW Constant Bitrate 5:1,
Blackmagic RAW Constant Bitrate 8:1,
Blackmagic RAW Constant Bitrate 12:1,
Blackmagic RAW Constant Bitrate 18:1,
Blackmagic RAW Constant Quality Q0,
Blackmagic RAW Constant Quality Q1,
Blackmagic RAW Constant Quality Q3,
Blackmagic RAW Constant Quality Q5.

Control

External Control

Blackmagic SDI Camera Control Protocol, iPad control, Bluetooth control, 1 x 2.5mm LANC for lens and record control.

Talkback and Tally

Talkback

SDI Channels 15/16 and iPhone headset.

Live Tally Indicator

Tally on LCD, URSA Viewfinder and URSA Studio Viewfinder.

Storage Features

Storage Type

2 x CFast 2.0

2 x SD UHS-II cards

1 x high speed USB-C expansion port for external media.

Storage Rates

Storage rates based on 24 frames per second.

12K - 12,288 x 6480

Blackmagic RAW 5:1 - 578 MB/s

Blackmagic RAW 8:1 - 361 MB/s

Blackmagic RAW 12:1 - 241 MB/s

Blackmagic RAW 18:1 - 160 MB/s

Blackmagic RAW Q0 - 241 to 578 MB/s¹

Blackmagic RAW Q1 - 144 to 361 MB/s²

s²

Blackmagic RAW Q3 - 96 to 241 MB/s³

s³

Blackmagic RAW Q5 - 72 to 180 MB/s⁴

s⁴

Blackmagic RAW Q0 - 107 to 258 MB/s¹

s¹

8K - 8192 x 4320

Blackmagic RAW 5:1 - 258 MB/s

Blackmagic RAW 8:1 - 161 MB/s

Blackmagic RAW 12:1 - 107 MB/s

Blackmagic RAW 18:1 - 72 MB/s

Blackmagic RAW Q0 - 107 to 258 MB/s¹

s¹

Blackmagic RAW Q1 - 64 to 161 MB/s²

s²

Blackmagic RAW Q3 - 43 to 107 MB/s³

s³

Blackmagic RAW Q5 - 32 to 81 MB/s⁴

s⁴

6K - 6144 x 3240

Blackmagic RAW 5:1 - 145 MB/s

Blackmagic RAW 8:1 - 91 MB/s

Blackmagic RAW 12:1 - 61 MB/s

Blackmagic RAW 18:1 - 40 MB/s

Blackmagic RAW Q0 - 61 to 145 MB/s¹

s¹

Blackmagic RAW Q1 - 36 to 91 MB/s²

Blackmagic RAW Q3 - 24 to 61 MB/s³

Blackmagic RAW Q5 - 18 to 45 MB/s⁴

s⁴

4K - 4096 x 2160

Blackmagic RAW 5:1 - 65 MB/s

Blackmagic RAW 8:1 - 41 MB/s

Blackmagic RAW 12:1 - 27 MB/s

Blackmagic RAW 18:1 - 18 MB/s

Blackmagic RAW Q0 - 27 to 65 MB/s¹

Blackmagic RAW Q1 - 16 to 41 MB/s²

Blackmagic RAW Q3 - 11 to 27 MB/s³

Blackmagic RAW Q5 - 8 to 20 MB/s⁴

s⁴

¹ Constant Quality setting Q0 storage rates quoted are indicative only, based on a 5:1 - 12:1 compression range.

Recording Formats

Blackmagic RAW Q0, Q1, Q3, Q5, 5:1,

8:1, 12:1 and 18:1 at 12,288 x 6480,

11,520 x 6480, 12,288 x 5112, 7680 x

6408, 8192 x 4320, 7680 x 4320, 8192

x 3408, 5120 x 4272, 6144 x 3240,

4096 x 2160, 3840 x 2160, 4096 x

1704 and 2560 x 2136 stored as

12 bit non-linear with film, extended

video, video or custom 3D LUT

embedded in metadata.

² Constant Quality setting Q1 storage rates quoted are indicative only, based on a 8:1 - 20:1 compression range.

³ Constant Quality setting Q3 storage rates quoted are indicative only, based on a 12:1 - 30:1 compression range.

⁴ Constant Quality setting Q5 storage rates quoted are indicative only, based on a 16:1 - 40:1 compression range.
Actual storage rates are entirely dependent on image subject matter.

Software

Software Included

URSA Mini Operating System

DaVinci Resolve Studio for Mac and Windows including activation key

Blackmagic Camera Setup


Blackmagic RAW Player

Blackmagic RAW QuickLook Plugin

Blackmagic RAW SDK

Blackmagic RAW Speed Test

Operating Systems



Mac 10.14 Mojave,
Mac 10.15 Catalina or later.



Windows 10.

Power Requirements

Power Supply

1 x External 12V power supply. 12 pin Molex connector for rear battery plate.

External Power Input

1 x 4 pin XLR port for external power or battery use.
1 x 12 pin Molex connector on rear battery plate.
Custom V-mount battery plate with D-tap +12V regulated output from camera.

Power

Rear camera mount compatible with industry standard V-mount or gold mount battery plates.

Accessories

Optional Accessories

URSA Mini Pro PL, EF and F Mounts
URSA Mini Pro Shim Kit
URSA Mini Shoulder Kit including top handle and extender arm
URSA Viewfinder
URSA Studio Viewfinder
URSA Mini Recorder
URSA VLock Battery Plate
URSA Gold Battery Plate
URSA Mini Mic Mount
URSA Mini Top Handle
URSA Handgrip
Blackmagic Camera Fiber Converter

Physical Specifications



Environmental Specifications

Operating Temperature

0° to 40°C (32° to 104°F)

Storage Temperature

-20° to 45°C (-4° to 113°F)

Relative Humidity

0% to 90% non-condensing

What's Included

Blackmagic URSA Mini Pro 12K Body
Turret dust cap
PL lens mount
Power supply
DaVinci Resolve Studio activation key

Warranty

12 Month Limited
Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2020, all rights reserved.
All trademarks are property of their respective owners. MSRP excludes VAT and local shipping costs.
This website uses remarketing services to advertise on third party websites to previous visitors to our site.
You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller