



# Specifications



**new!**



**new!**



	<b>Video 25 Plus</b> EFP/OB	<b>Video 20 S1</b> EFP/ENG	<b>Video 18 S1</b> EFP/ENG	<b>Video 15 SB</b> ENG	<b>DV 12 SB</b> ENG
<b>Code</b>	2500P	2010	1810	1505	1205
<b>Weight</b>	4.5 kg / 9.9 lb	3.4 kg / 7.5 lb	3.3 kg / 7.3 lb	2.8 kg / 6.2 lb	2.7 kg / 6.0 lb
<b>Payload</b>	8–35 kg / 18–77 lb	2–25 kg / 4–55 lb	2–18 kg / 4–40 lb	1–16 kg / 2–35 lb	1–14 kg / 2–30 lb
<b>Balance plate / Sliding range</b>	110 mm / 4.3"	120 mm / 4.7"	120 mm / 4.7"	70 mm / 2.8"	70 mm / 2.8"
<b>Counterbalance steps</b>	18	16 + Boost Button	16 + Boost Button	12	12
<b>Grades of drag</b>					
horizontal steps	7 + 0	7 + 0	7 + 0	7 + 0	5 + 0
vertical steps	7 + 0	7 + 0	7 + 0	7 + 0	5 + 0
<b>Tilt range</b>	+90°/-75°	+90°/-70°	+90°/-70°	+90°/-75°	+90°/-75°
<b>Temperature range</b>	-40/+60 °C -40/+140 °F	-40/+60 °C -40/+140 °F	-40/+60 °C -40/+140 °F	-40/+60 °C -40/+140 °F	-40/+60 °C -40/+140 °F
<b>Camera fitting</b>					
Touch & Go® plate	16	16	16	16	16
Sideload plate S	—	—	—	—	—
<b>Tripod/Pedestal fitting</b>					
Bowl	150 mm	100 mm	100 mm	100 mm	100 mm
Flat Base	Integrated	—	—	Integrated	Integrated
<b>Pan bar(s)</b>					
Type	Plus	Plus	Plus	DV right	DV 100
Number	2	1	1	1	1
telescopic	•	•	•	•	—
Attachment (front/rear/handle)	Ø 18/22/32 mm Ø 0.7/0.9/1.3"	Ø 18/22/32 mm Ø 0.7/0.9/1.3"	Ø 18/22/32 mm Ø 0.7/0.9/1.3"	Ø 18/22/32 mm Ø 0.7/0.9/1.3"	Ø 18/-/32 mm Ø 0.7/-/1.3"
Length	350–520 mm 13.8–20.5"	350–520 mm 13.8–20.5"	350–520 mm 13.8–20.5"	350–520 mm 13.8–20.5"	450 mm 17.7"
<b>Adapter viewfinder extension / adapter block</b>					
standard	•	—	—	—	—
optional	—	•	•	•	•
<b>Level</b>					
Self-illuminating Touch Bubble	•	•	•	•	•
Batteries 3 x 625 U or LR9	•	—	—	•	•
Battery 1 x CR 2032	—	•	•	—	—
<b>Systems</b>	25 EFP 2 CF	20 S1 SL HD MCF 20 S1 SL HD CF 20 S1 HD MCF 20 S1 HD CF 20 S1 ENG 2 CF	18 S1 SL MCF 18 S1 SL CF 18 S1 ENG 2 MCF 18 S1 ENG 2 CF 18 S1 ENG 2 D	15 SB C III 15 SB SL MCF 15 SB ENG 2 MCF 15 SB ENG 2 CF 15 SB ENG 2 D	12 SB SL MCF 12 SB ENG 2 MCF 12 SB ENG 2 CF 12 SB