



Technische Daten



	Video 25 Plus EFP / AÜ	Video 20 S1 EFP / EB	Video 18 S1 EFP / EB	Video 15 SB EB	DV 12 SB EB
Code	2500P	2010	1810	1505	1205
Gewicht	4,5 kg	3,4 kg	3,3 kg	2,8 kg	2,7 kg
Traglast	8–35 kg	2–25 kg	2–18 kg	1–16 kg	1–14 kg
Balanceplatte / Verschiebereich	110 mm	120 mm	120 mm	70 mm	70 mm
Gewichtsausgleich Stufen	18	16 + Boost Button	16 + Boost Button	12	12
Dämpfung					
horizontal	7 + 0	7 + 0	7 + 0	7 + 0	5 + 0
vertikal	7 + 0	7 + 0	7 + 0	7 + 0	5 + 0
Neigebereich	+90°/-75°	+90°/-70°	+90°/-70°	+90°/-75°	+90°/-75°
Temperaturbereich	-40/+60 °C	-40/+60 °C	-40/+60 °C	-40/+60 °C	-40/+60 °C
Kameraanschluss					
Touch & Go® Platte	16	16	16	16	16
Sideload-Platte	—	—	—	—	—
Stativ-/ Pedestalanschluss					
Schale	150 mm	100 mm	100 mm	100 mm	100 mm
Flachboden	Integriert	—	—	Integriert	Integriert
Schwenkarm(e)					
Typ	Plus	Plus	Plus	DV rechts	DV 100
Anzahl	2	1	1	1	1
ausziehbar	•	•	•	•	—
Befestigung (vorne/hinten/Griff)	Ø 18/22/32 mm	Ø 18/22/32 mm	Ø 18/22/32 mm	Ø 18/22/32 mm	Ø 18/32 mm
Länge	350–520 mm	350–520 mm	350–520 mm	350–520 mm	450 mm
Adapter Sucherlupenstütze/ Adapterklotz					
standard	•	—	—	—	—
optional	—	•	•	•	•
Libelle					
Selbstleuchtende Touch Bubble	•	•	•	•	•
Batterien 3 x 625 U oder LR9	•	—	—	•	•
Batterien 1 x CR 2032	—	•	•	—	—
Systeme	25 EFP 2 CF	20 S1 SL HD MCF 20 S1 SL HD CF 20 S1 HD MCF 20 S1 HD CF 20 S1 ENG 2 CF	18 S1 SL MCF 18 S1 SL CF 18 S1 ENG 2 MCF 18 S1 ENG 2 CF 18 S1 ENG 2 D	15 SB C III 15 SB SL MCF 15 SB ENG 2 MCF 15 SB ENG 2 CF 15 SB ENG 2 D	12 SB SL MCF 12 SB ENG 2 MCF 12 SB ENG 2 CF 12 SB