



DMON-4S

Quad (3G/HD/SD)-SDI to HDMI
Multiviewer and Converter



PRODUCT FEATURES

- Includes 4 independent mini HDMI outputs that can each output any of the four (3G/HD/SD)-SDI inputs or a Quad-Split of all them.
For example you could use the unit to have:
 - 4 independent SDI to HDMI converters
 - 3 independent SDI to HDMI converters with a quad-split output
 - 2 independent SDI to 2 x HDMI converters with loop through
 - A single SDI or Quad-Split to 4 x HDMI outputs
- Inputs 2 and 4 can be individually changed to output active loop copies of inputs 1 and 2 respectively.
- Quad-Split mode allows selection of audio from any input.
- The DMON-4S is a truly portable converter, that incorporates our new easy to use LCD and button control system. This gives you easy access to all of the amazing features without using complicated LED/button control, dip switches or having to carry around a computer to change a simple setting.
- This unit also includes:
 - USB port for control and firmware updates
 - Heavy duty metal box
 - Metal Thread Locking DC Power Socket
 - Power Supply, HDMI Cable and USB Cable

SPECIFICATIONS

SDI INPUT FORMATS	3G: SMPTE 424M@2.97 and 2.967Gb/s • 1080p@60/59.94/50Hz HD: SMPTE 292M/274M/296M@1.485 and 1.435Gb/s • 1080i@60/59.94/50Hz • 1080p/psf@30/29.97/25/24/23.98Hz • 720p@60/59.94/50/30/29.97/25/24/23.98Hz SD: SMPTE 259M@270Mb/s • 625i50 • 525i59.94	LCD / BUTTON MENU OPTIONS	• Status for all 4 inputs • HDMI output type and source selection from SDI inputs 1 to 4 • Quad-Split output format selection • Quad-Split output aspect and type of 16:9 or 4:3 at either 90 or 100% of screen size • Quad-split individual aspect format for each input of Same as output, Letter-box or Pillar-box • Quad-split Border Enable • Quad-split mode reference of either Free-run or inputs 1 to 4
HDMI OUTPUT FORMATS	• 1080p@60/59.94/50Hz • 1080i@60/59.94/50Hz • 1080p@30/29.97/25/24/23.98Hz • 720p@60/59.94/50/30/29.97/25 • 625i50 • 525i59.94	INPUTS	• Up to 4 x (3G/HD/SD)-SDI Inputs • Input Equalization > 100M using Belden 1694A • USB for control and updates
POWER	• +5V to +32V DC, 6 Watts • Positive Centre Pin	OUTPUTS	• 4 x mini HDMI Type C • Optional SDI Active Loop Out of inputs 1 and/or input 3
		DIMENSIONS	79.5mm x 123mm x 29.5mm (3.1" x 4.8" x 1.2")

DISTRIBUTED BY:

Symbiosis EU -
www.symbiosis.eu



www.decimator.com
FUTURE-PROOF SOLUTIONS

Copyright © 2013 DECIMATOR DESIGN PTY LTD DMON-4S BROCHURE V1.0