

Teranex Mini SDI Distribution 12G



Distribute a single SDI video input to up to eight SDI outputs. Features the latest multi rate 12G-SDI connections with full SDI re-clocking allowing the converter to automatically switch between all SD, HD and Ultra HD formats up to 2160p60. Perfect for distributing a single SDI signal to multiple devices such as monitors, switchers and encoders.

\$495

Connections

SDI Video Input

1 x 12G-SDI SD/HD/2K/4K auto switching.

Multi Rate Support

Automatic switching between SD/HD/2K and 4K

Re-Clocking


Yes

SDI Video Output

8 x 12G-SDI automatically matches the SD/HD/2K/4K 12G-SDI input

Updates and Configuration

USB or Ethernet



Standards

SD Format Support

525i29.97 NTSC, 625i25 PAL

Ultra HD Format Support

2160p23.98, 2160p24, 2160p25, 2160p29.97, 2160p30, 2160p50, 2160p60.

HD Format Support

720p50, 59.94, 60
1080p23.98, 24, 25, 29.97, 30, 50, 59.94, 60
1080PsF23.98, 24
1080i50, 59.94, 60

2K Format Support

1080p23.98, 24, 25
1080PsF23.98, 24, 25

4K Format Support

2160p23.98, 2160p24, 2160p25,
2160p29.97, 2160p30.

SDI Compliance

SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 372M, SMPTE 424M, SMPTE 425M, SMPTE 2081-1, SMPTE 2081-10, SMPTE 2082-1, SMPTE 2082-10

SDI Video Rates

SDI video connections are switchable between standard definition, high definition level A and level B 3G-SDI, 6G-SDI and 12G-SDI.

SDI Video Sampling

4:2:2 and 4:4:4

SDI Audio Sampling

Television standard sample rate of 48 kHz and 24-bit.

SDI Color Space

YUV & RGB

Software

Software Control

Mac OS X™ and Windows™ software upgrade via USB and Ethernet.

Internal Software Upgrade

Via included updater application.

Operating Systems



Mac OS X 10.10 Yosemite,
Mac OS X 10.11 El Capitan
or later.



Windows 8.1 or
Windows 10.

Settings Control

Basic Settings Control

Mini Switches, USB and Ethernet via free software utility.

Optional Front Panel Control

Front mounted Smart Panel with LCD, rotary knob and six settings buttons.

Power Requirements

Power Supply

1 x built-in international AC power supply with IEC C14 inlet. IEC Power cable required. 90 - 240V AC Input.

Power Over Ethernet

Can be powered via 48V DC using PoE+ (power over ethernet).


Power Consumption

16 Watts

Operational Voltage Range

90 - 240V AC

Physical Specifications



Environmental Specifications

Operating Temperature

0° to 40°C (32° to 104°F)

Storage Temperature

-20° to 60°C (-4° to 140°F)

Relative Humidity

0% to 90% non-condensing

What's Included

Teranex Mini - SDI Distribution 12G

SD card with software and manual

Warranty

3 year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2016, all rights reserved.
All trademarks are property of their respective owners. MSRP excludes sales taxes/duties and shipping costs.

Blackmagic Design Authorized Reseller