


Studio Wall Monitors

SWM-550A *New!*



Main body Dimensions

- Main Body : 1262.4 x 732 x 95.5 (mm) / 49.7 x 28.81 x 3.75 (inch)
- Weight : TBD



LCD

Size	54.6"
Resolution	1920 x 1080 (16 : 9)
Pixel Pitch	0.63mm
Color Depth	1.07B
Viewing Angle (Typ.)	178°(H) / 178°(V)
Luminance (Max.)	700cd / m ²
Contrast Ratio	4000:1
Display Area	1209(H) x 680(V) mm

A brand-new Studio Wall Monitor

The SWM series monitors are newly designed for the best match for the studio walls. A clean bezel with only a power button and a small indication lamp secures the best monitoring condition for the users. Along with the traditional interfaces of SDI, HDMI and DVI, the optical fiber interface has been added for the user's choice. It supports video formats up to 3G-SDI and professional features such as Marker, Timecode, Audio Level Meter, various CCs and UMDs.



Product Highlights

- 55" 1920 x 1080 (16:9) Resolution
- 3G-SDI Level A/B
- Audio Level Meter Display
- Blue Only
- H/V Delay
- Marker
- Mono
- Time Code Display
- UMD
- User Aspect
- CC-608 ANC
- CC-608 LINE 21
- CC-708
- CC-KOR
- OP42
- OP47

Input

1 x DVI-I	DVI IN
1xHDMI	HDMI Input
2xBNC	SDI A/B Channel Input
1xOPTIC	Optical Input(Optional)

Output

2xBNC	SDI A/B Channel (Active Through Out)
-------	--------------------------------------

Input Signal

3G SDI	2.970Gbps
HD-SDI	1.485Gbps
SD-SDI	270Mbps
HDMI	480i / 480p / 576i / 576p / 720p / 1080i / 1080p / 640x480 / 720x400 / 800x600 / 1024x768 / 1280x1024 / 1600x1200
DVI-D (PC mode)	640x480/720x400/800x600/1024x768/1280x1024/1366x768/1600x1200/1920x1200
DVI-D (HDMI mode)	1080p(24/25/30/50/60)/1080i(50/60)/720p(50/60)/480i(60)/480p(60)/576i(50)/576p(50)
OPTICAL	2.970Gbps / 1.485Gbps / 270Mbps

SDI Input Signal Formats

SMPTE-425M-A/B	1080i (60/59.94/50)
	1080p (60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
SMPTE-372M (Dual Link)	Dual HD-SDI 1080p (60/59.94/50) YCbCr(4:2:2)
	Dual HD-SDI 1080i (60/59.94/50) YCbCr/RGB(4:4:4) 1080p (30/29.97/25/24/24sF/23.98/23.98sF)
SMPTE-274M	1080i (60 / 59.94 / 50)
	1080p (30/29.97/25/24/24sF/23.98/23.98sF)
SMPTE-296M	720p (60/59.94/50)
SMPTE-260M	1035i (60/59.94)
SMPTE-125M	480i (59.94)
ITU-R BT.656	576i (50)
2K Format	2048 x 1080p (24/24sF/23.98/23.98sF)
Audio IN	-
Audio OUT	-
Power	AC 100~240V (50~60Hz)
Power Consumption (Approx.)	TBD
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Accessory	AC Power Cord / USB Cover

* Specifications may be changed without notice.

Optional Accessories

