

DP-V1710**PANEL**

Panel type	IPS LCD panel
Screen size	17.3 inch (43.8cm)
Aspect ratio	16:9
Resolution	3840 x 2160 (8.3 megapixels)
Active display area	Approx. 381.9 x 214.8mm
Pixel pitch	99µm / 255 ppi

IMAGE QUALITY

Brightness - standard	100 cd/m2
Viewing angle (up, down, left, right)	89°(Contrast ratio 10:1 or higher)
Surface treatment	Anti-glare coating

GENERAL

Backlight type	LED, Matrix Array
Power - Rated voltage	AC 100~240 V DC 12 VMax.10 A, XLR terminal
Power - Rated frequency	50/60Hz
Environmental conditions - operating	Temperature and humidity: 0 to 40°C (32 -104°F)(20-85 % RH no condensation) recommended: 15-30 °C (59 -86 °F) Pressure: 700-1060 hPa
Environmental conditions - storage/transporting	Temperature and humidity: -20 to 40°C (-4 -104°F)(20-85 % RH no condensation) 41 to 60°C (105 -140°F)(20-30% RH no condensation) Pressure: 700-1060 hPa
Dimensions (width ×height ×depth)	With stand and handle: Approx. 435×356×194 mm (17.1×14.0×7.6 in.) Display unit only, without protruding parts: Approx. 435×308×154 mm (17.1×12.1×6.1 in.)
Weight	Approx. 8 kg
Mounting hole pitch	VESA standard 100x100 mm (3.9 ×3.9 in)

INTERFACE		
	Input - 6G/3G/HD-SDI	4 (1system) BNC (75Ω) receptacle terminal 6G-SDI : SMPTE 2081 compliant 3G-SDI : SMPTE 2048-2/274M/296/372/425-5/425-3/425-1/428-19/428-9 compliant HD-SDI : SMPTE 2048-2/274M/292-1/296/428-19/428-compliant
	Input - HDMI	1 (1 system) Type A terminal Copy protection: HDCP 2.2
	Output - 6G/3G/HD-SDI	4 (pass-through 1 system)
	Output - headphone	1 Stereo mini-jack, Supported impedance: 32Ω to 64Ω
	Others - USB	1 USB A receptacle terminal Universal Serial Bus Specification Revision 2.0 compliant LS (Low Speed)/FS (Full Speed)/HS (High Speed) mode compatible Enhanced Host Controller Interface Specification for Universal Serial Bus Revision 1.0 compliant
	Others - LAN	1 RJ-45 terminal IEEE802.3 10BASE-TX/IEEE802.3u 100BASE-Tx compliant
	Others - REMOTE	1 RJ-45 terminal, GPI 8pin
OTHER		
	Tally lamp	Red / Green / Amber

**All data is based on Canon standard testing methods except where indicated.
Subject to change without notice.**