

RGBlink vue PTZ camera



Front View



Rear View



Left View

Key Features

- High speed optical zoom
- Low-Latency SRT Upload to Cloud
- High performance in low light scenarios with Wide Dynamic Range
- Full 1920x1080p HD Resolutions up to 60 frames per second
- H.265/H.264 Dual Stream Output Adapted to Different Network Environments
- Pan and Tilt Control
- Optional interface
- Optional 12X/20X/30X optical zoom
- Wide Application
- Low-power Sleep Function
- Support TALLY
- Support PoE

Specification

Interface	Output	3G SDI	1xBNC				
		HDMI	1xHDMI-A				
		USB	1xUSB-A				
		LAN	1xRJ45				
	Audio	IN	1x3.5mm Stereo Jack				
	Control	RS232 IN/OUT	2xDIN8				
		RS485	1x4pin Terminal				
	Power		1xDC12V Jack				
Performance	Camera	Optical Zoom	f=3.9~46.8mm	20X	f=5.5~110mm	30X	f=5.2~148.4mm
		View Angle	6.3°~72.5°		3.3°~54.7°		2.14°~58.1°
		AV	F1.8 ~ F2.4		F1.6 ~ F3.5		F1.3 ~ F4.8
		Digital Zoom		10X			
		Minimum Illumination		0.5Lux (F1.8, AGC ON)			
		DNR		2D & 3D DNR			
		White Balance		Auto/Manual/One Push/3000K to 7000K(selectable)			
		Focus		Auto/Manual			
		Aperture/Electronic Shutter		Auto/Manual			
		BLC		ON/OFF			
	WDR		OFF/Dynamic Level Adjustment				
	Video Adjustment		Brightness/Color/Saturation/Contrast/Sharpness/B/W mode/Gamma curve				
			SNR	>55dB			
			Effective Pixels	2.07m,16:9			
		Pan-and-Tilt Parameter	Pan/Tilt Movement	-170°~+170°/-30°~+90°			
	Pan/Tilt Control Speed		0.1~60°/S; 0.1~30°/S				
	Preset Speed/Quantity		Pan:60°/S, Tilt:30°/S; Up to 255 preset positions (10 remote control)				
		360° TALLY	full 360° view of TALLY				
	Audio Compression Format	AAC MP3 G.711A					
	Video Compression Format	H.264 H.265 Dual Streaming Output					
	Output Resolutions	1080p60/59.94/50/30/29.97/25 1080i60/59.94/50 720p60/59.94/50					
	Control Protocol	VISCA Pelco-D Pelco-P					
	Baud Rate(bps)	115200 9600 4800 2400bps					
	Network Protocol	RTSP RTMP SRT ONVIF					
	Supported Standards	SDI SMPTE 425M (Level A & B) SMPTE 424M SMPTE 292M SMPTE 259M-C DVB-ASI					
Power	Input Voltage	DC12V/1.5A					
	Max Power	12W					
Environment	Temperature	-10℃~50℃					
	Humidity	20%~80%					
Physical	Weight	Net 1.7kg					
	Dimension	Net 180mm(front)x188mm(side)x198mm(height)					

Order Codes

Product Code	Item
981-0011-27-0	RGB20X-POE-TLY
981-0011-28-0	RGB20X-PNDI-TLY
981-0011-29-0	RGB20X-USB-TLY
981-0011-31-0	RGB12X-POE-TLY
981-0011-32-0	RGB12X-PNDI-TLY
981-0011-33-0	RGB30X-POE-TLY
981-0011-34-0	RGB30X-PNDI-TLY

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgbink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China
Specifications are correct at time of printing and subject to change or alteration without notice.

RGBlink



www.rgbink.com