

## Mini Converter SDI to Audio 4K



Mini Converter SDI to Audio 4K includes everything you need to de-embed 4 channels of analog audio or 8 channels of AES/EBU digital audio from any SDI video connection. Now you can access the audio in any SDI video connection for output to a massive range of audio equipment such as audio mixers, analog broadcast decks, audio monitors and more!

**\$295**

### Connections

#### SDI Video Input

Switchable between SD, HD, 3G and 6G-SDI.

#### SDI Video Output

Automatically matches the SD, HD, 3G and 6G-SDI video input.

#### SDI Redundant Input

Automatically switches over if main SDI input is lost.

#### Analog Audio

4 channels of professional balanced analog audio with standard 1/4 inch jack connections.

#### AES/EBU Digital Audio

8 channels of professional balanced digital with standard 1/4 inch jack connections.

#### Multi Rate Support


Auto detection of 4K, UHD, 2K, HD or SD-SDI inputs.

#### Updates and Configuration

USB

#### Reclocking

Yes



### Standards

#### SDI Compliance

SMPTE 292M, SMPTE 259M, SMPTE 296M, SMPTE 372M, SMPTE 424M-B, SMPTE 425M, SMPTE ST-2081, ITU-R BT.656, ITU-R BT.601.

#### SDI Audio Sampling

Television standard sample rate of 48 kHz and 24 bit.

#### SDI Color Precision

4:2:2, 4:4:4

#### SDI Color Space

YUV, RGB

---

#### SDI Video Rates

SDI video connections are switchable between standard definition and high definition.

#### SDI Video Sampling

4:2:2, 4:4:4

#### SDI Auto Switching

Automatically selects between SD, HD, 3G and 6G-SDI.

#### SDI Format Support

525/29.97 NTSC, 525/23.98 NTSC, 625/25 PAL, 720p50, 720p59.94, 720p60, 1080i50, 1080i59.94, 1080i60, 1080p23.98, 1080PsF23.98, 1080p24, 1080PsF24, 1080p25, 1080PsF25, 1080p29.97, 1080PsF29.97, 1080p30 and 1080PsF30, 1080p50, 1080p59.94, 1080p60, 2048 x 1080p23.98, 2048 x 1080p24, 2048 x 1080p25, 2048 x 1080PsF23.98, 2048 x 1080PsF24, 2048 x 1080PsF25, 3840 x 2160p23.98, 3840 x 2160p24, 3840 x 2160p25, 3840 x 2160p29.97, 3840 x 2160p30, 4096 x 2160p23.98, 4096 x 2160p24, 4096 x 2160p25, 4096 x 2160p29.97, 4096 x 2160p30.

---

### Software

#### Software Control

Mac OS X™ and Windows™ software upgrade via USB.

#### Internal Software Upgrade

Via included updater application.

---

### Operating Systems



Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan or later.



Windows 8.1 or Windows 10.

---

### Settings Control

Mini Switches or USB software.

---

### Power Requirements

#### Power Supply

+12V universal power supply included with international socket adapters for all countries. Cable tie point.

#### Power Consumption

5.52 Watts

#### Operational Voltage Range

12V - 31V DC

---

## Physical Specifications



---

## Environmental Specifications

**Operating temperature**  
0° to 40° C (32° to 104° F)

**Storage temperature**  
-20° to 60° C (-4° to 113° F)

**Relative Humidity**  
0% to 90% non-condensing

---

## What's Included

Mini Converter SDI to Audio 4K  
12V universal power supply with international socket adapters

---

## Warranty

3 Year Limited Manufacturer's Warranty.

---

All items on this website are copyright Blackmagic Design Pty. Ltd. 2016, all rights reserved.  
All trademarks are property of their respective owners. MSRP excludes sales taxes/duties and shipping costs.

Blackmagic Design Authorized Reseller