

Teranex Mini HDMI to Optical 12G



Convert from HDMI to 12G optical fiber and 12G-SDI. Works with all video formats including SD, HD, 6G and 12G-SDI rates and includes an up converter for converting HD to Ultra HD. Embed audio from balanced analog or AES/EBU and timecode input. Ideal for converting HDMI consumer cameras to SDI, or adding SDI outputs to computers with HDMI connections.

\$895

Connections

HDMI

1 x HDMI 2.0 type A connector with support for 2160p60.

Optical Fiber Connection

LC connector, 1310 nanometer wavelength, single mode.

Optical Fiber Video Output

Automatically matches the SD, HD and 12G-SDI HDMI video input.

SDI Video Output

Automatically matches the SD, HD and 12G-SDI HDMI video input.

Analog Audio Input

2 channels professional balanced analog audio via XLR connectors. Right XLR can be configured for timecode input.

AES/EBU Audio Input

4 channels professional 110Ω balanced digital audio via XLR connectors. Right XLR can be configured for Timecode input.

Multi Rate Support


Automatic switching between SD/HD/2K and 4K.

Updates and Configuration

USB and Ethernet.

Re-Clocking

Yes



Optical Output Formats

SD Format Support

525i29.97 NTSC, 625i25 PAL

HD Format Support

720p50, 59.94, 60
1080p23.98, 24, 25, 29.97, 30, 50, 59.94, 60
1080i50, 59.94, 60

2K Format Support

1080p23.98, 24, 25

Ultra HD Format Support

2160p23.98, 24, 25, 29.97, 30, 50, 59.94, 60

4K Format Support

2160p23.98, 24, 25, 29.97, 30

SDI Compliance

SMPTE 292M, SMPTE 259M, SMPTE 296M, SMPTE 372M, SMPTE 424M, SMPTE 425M, SMPTE 297M for Optical Fiber SDI, SMPTE 2081-1, SMPTE 2081-10, SMPTE 2082-1, SMPTE 2082-10

SDI Video Rates

SDI video connections are switchable between standard definition, high definition level A and level B 3G-SDI, 6G-SDI and 12G-SDI.

SDI Video Sampling

4:2:2 and 4:4:4.

SDI Audio Sampling

Television standard sample rate of 48 kHz and 24-bit.

SDI Color Precision

YUV 4:2:2 and RGB 4:4:4 in HD, 2K and 4K.

SDI Color Space

REC 601, REC 709

HDMI Input Formats

SD Format Support

525i29.97 NTSC, 625i25 PAL

HD Format Support

720p50, 59.94, 60
1080p23.98, 24, 25, 29.97, 30, 50, 59.94, 60
1080i50, 59.94, 60

Ultra HD Format Support

2160p23.98, 24, 25, 29.97, 30, 50, 59.94, 60

4K Format Support

2160p23.98, 24, 25, 29.97, 30

HDMI Color Space

REC 601, REC 709

HDMI Color Precision

YUV 4:2:2 and RGB 4:4:4 in HD, 2K and 4K.

Copy Protection

HDMI input is unable to capture from copy protected HDMI sources. Always confirm copyright ownership before capture or distribution of content.

Software

Software Control

Mac OS X™ and Windows™ software upgrade via USB or Ethernet.

Internal Software Upgrade

Via included updater application.

Operating Systems



Mac OS X 10.10 Yosemite,
Mac OS X 10.11 El Capitan
or later.



Windows 8.1 or
Windows 10.

Settings Control

Basic Settings Control

Mini Switches, USB and Ethernet via free software utility.

Optional Front Panel Control

Front mounted Smart Panel with LCD, rotary knob and six settings buttons.

Power Requirements

Power Supply

1 x built-in international AC power supply with IEC C14 inlet. IEC Power cable required. 90 - 240V AC Input.

Power Over Ethernet

Can be powered via 48V DC using PoE+ (power over ethernet).


Power Consumption

16 Watts

Operational Voltage Range

90 - 240V AC

Physical Specifications



Environmental Specifications

Operating Temperature

0° to 40°C (32° to 104°F)

Storage Temperature

-20° to 60°C (-4° to 140°F)

Relative Humidity

0% to 90% non-condensing

What's Included

Teranex Mini - HDMI to Optical 12G
SD card with software and manual

Warranty

3 year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2016, all rights reserved.
All trademarks are property of their respective owners. MSRP excludes sales taxes/duties and shipping costs.

Blackmagic Design Authorized Reseller