

sachtler

FSB 14T Mk II

Sachtler FSB14T Mk II Fluid Head with Touch & Go Camera Plate and Pan Bar – Payload range: 0-16 kg / 0-35.3 lb

SKU: S2077-0002

Fluid, Smooth, Balanced: Capture the moment precisely

Redesigned with features from the revolutionary Sachtler aktiv fluid head range, FSB delivers precision movement with finely calibrated levels of drag and counterbalance for the perfect shot. The streamlined profile is built to withstand the toughest conditions to deliver repeatable, reliable camera support shot after shot.



Product Highlights

- **Smooth operation.**
Create precision pans with smooth starts and soft stops.
- **Finely balanced.**
Delivering smooth pan-tilt fluid actions to match any camera payload from 0kg.
- **Always on the level.**
Innovative illuminated PrismBubble visible from any height – day or night.
- **Built for endurance.**
Engineered to the highest standards with tough materials and precision components, FSB is built for endurance.



Technical Specifications

Feature	Value
Range	FSB
Payload	0 to 16 kg
Counterbalance	15 + 0 steps
Drag	7 + 0 drag settings
Weight	3.20 kg
Pan bar length	350 to 520 mm
Pan bar type	Pan bar DV right (telescopic)
Pan bar attachment	18/22/32 mm
Pan bar count	1, telescopic
Level bubble	Yes, illuminated
Battery type	CR2032
Adaptor viewfinder extension	No Adaptor
Bowl size	100 mm
Camera plate	Touch & Go plate 16
Temperature range	-40 to 60 °C
Tilt range	+90° to -70°
Sliding range	70 mm
Interface Compatibility	Touch & Go



What's in the box?

FSB 14T Mk II fluid head with telescopic pan bar DV and Touch & Go plate 16

- Pan bar DV right (telescopic)
- Touch & Go Plate 16



Payload Diagram FSB 14T Mk II

