

The world's fastest tripod.

Multi-award winning **flowtech™** is incredibly fast, lightweight and easy to set up and adjust compared to any other tripod. Giving you ultimate versatility with an improved workflow.

Performance tested in extreme conditions, **flowtech™** is a revolution in tripod technology. Try it and join the revolution.

- ▷ **Deploy and adjust your tripod in an instant:** Unique quick release brakes
- ▷ **Easy to transport and exceptional torsional stiffness:** Ergonomic carbon fibre leg design
- ▷ **Capture extremely low and high shots:** Versatile hinge lock mechanism
- ▷ **Superior performance and reliability:** Extensive endurance and environmental testing

flowtech™

75mm 100mm



sachtler

Vinten

SKU	flowtech75 MS 4585	flowtech75 GS 4587	flowtech100 MS 5585	flowtech100 GS 5587	flowtech75 MS V4150-0003	flowtech75 GS V4150-0002	flowtech100 MS V4160-0003	flowtech100 GS V4160-0002
Payload	20kg / 44lb	20kg / 44lb	30kg / 66lb	30kg / 66lb	20kg / 44lb	20kg / 44lb	30kg / 66lb	30kg / 66lb
Spreader material	Lightweight	With foot operation and detachable rubber feet	Carbon fibre, adjustable angles	With foot operation and detachable rubber feet	Lightweight	With foot operation and detachable rubber feet	Carbon fibre, adjustable angles	With foot operation and detachable rubber feet
Weight (Tripod only)	2.9kg / 6.4lb	2.9kg / 6.4lb	3.2kg / 7.1lb	3.2kg / 7.1lb	2.9kg / 6.4lb	2.9kg / 6.4lb	3.2kg / 7.1lb	3.2kg / 7.1lb
Weight (Tripod with rubber feet and spreader)	3.5kg / 7.7lb	3.8kg / 8.4lb	4.1kg / 9.1lb	4kg / 8.8lb	3.5kg / 7.7lb	3.8kg / 8.4lb	4.1kg / 9.1lb	4kg / 8.8lb
Spreaderless mode height range	26 - 153cm 10.2 - 60.2in	26 - 153cm 10.2 - 60.2in	26 - 153cm 10.2 - 60.2in	26 - 153cm 10.2 - 60.2in	26 - 153cm 10.2 - 60.2in	26 - 153cm 10.2 - 60.2in	26 - 153cm 10.2 - 60.2in	26 - 153cm 10.2 - 60.2in
Spreader height range	63 - 157cm 24.8 - 61.8in	41 - 158cm 16.1 - 62.2in	52 - 155cm 20.5 - 61in	43 - 159 cm 16.9 - 62.6in	63 - 157cm 24.8 - 61.8in	41 - 158cm 16.1 - 62.2in	52 - 155 cm 20.5 - 61in	43 - 159cm 16.9 - 62.6in



**Mid-level
spreader
Systems**



Ace XL FT 75 1017MS	FSB 4 FT MS 0395	FSB 6 FT MS 0495	FSB 6 T FT MS 0465	FSB 8 FT MS 0795	FSB 8 T FT MS 0765	SKU	FSB 10 FT MS S2045FTMS	FSB 10 T FT MS S2046FTMS	DV 12 FT MS 1205FTMS	Video 15 FT MS 1505FTMS	Video 18 FT MS 1811FTMS	Cine 7+7 FT MS 1910FTMS
2 - 8kg 4.4 - 17.6lb	0 - 4kg 0 - 8.8lb	1.5 - 8kg 3.3 - 17.6lb	1.5 - 8kg 3.3 - 17.6lb	1 - 10kg 2.2 - 22lb	1 - 10kg 2 - 22lb	Payload range	4 - 12kg 8.8 - 26.5lb	4 - 12kg 8.8 - 26.5lb	1 - 15kg 2 - 33lb	1 - 17kg 2 - 37lb	2 - 22kg 4 - 48lb	2 - 22kg 4 - 48lb
8 steps	5 steps + 0	10 steps	10 steps	10 steps	10 steps	Counterbalance	10 steps	10 steps	12 steps	12 steps	16 steps + boost button	16 steps + boost button
3 / 3 + 0	3 / 3 + 0	3 / 3 + 0	3 / 3 + 0	5 / 5 + 0	5 / 5 + 0	Drag	5 / 5 + 0	5 / 5 + 0	5 / 5 + 0	7 / 7 + 0	7 / 7 + 0	7 / 7 + 0
104mm / 4.1in	120mm / 4.7in	120mm / 4.7in	60mm / 2.4in	120mm / 4.7	60mm / 2.4in	Balance range	120mm / 4.7in	60mm / 2.4in	70mm / 2.8in	70mm 2.8in	150mm / 5.9in	150mm / 5.9in
Ace Plate	Sideloading S	Sideloading S	Touch & Go S	Sideloading S	Touch & Go S	Camera fitting	Sideloading S	Touch & Go	Touch & Go	Touch & Go	Touch & Go	Sideloading M
5.3kg / 11.7lb	5.8kg / 12.8lb	6kg / 13.2lb	6.1kg / 13.4lb	6.1kg / 13.4lb	6.2kg / 13.7lb	Weight	6.8kg / 15lb	6.9kg / 15.2lb	7.3kg / 16.1lb	7.4kg / 16.3lb	8.2kg / 18.1lb	8.3kg / 18.3lb
41 - 169cm 16.1 - 66.5in	41 - 169cm 16.1 - 66.5in	41 - 169cm 16.1 - 66.5in	41 - 169cm 16.1 - 66.5in	41 - 169cm 16.1 - 66.5in	41 - 169cm 16.1 - 66.5in	Height range in spreaderless mode	41 - 170cm 16.1 - 66.9in	41 - 170cm 16.1 - 66.9in	41 - 170cm 16.1 - 66.9in	41 - 170cm 16.1 - 66.9in	42 - 172cm 16.5 - 67.7in	41 - 170cm 16.1 - 66.9in
78 - 173cm 30.7 - 68.1in	78 - 173cm 30.7 - 68.1in	78 - 173cm 30.7 - 68.1in	78 - 173cm 30.7 - 68.1in	78 - 173cm 30.7 - 68.1in	78 - 173cm 30.7 - 68.1in	Height range with mid-level spreader	71 - 172cm 28 - 67.7in	71 - 172cm 28 - 67.7in	71 - 172cm 28 - 67.7in	71 - 172cm 28 - 67.7in	72 - 173cm 28.3 - 68.1in	71 - 172cm 28 - 67.7in



**Ground
spreader
Systems**



Ace XL FT 75 GS 1017GS	FSB 4 FT GS 0396	FSB 6 FT GS 0496	FSB 6 T FT GS 0466	FSB 8 FT GS 0796	FSB 8 T FT GS 0766	SKU	FSB 10 FT GS S2045FTGS	FSB 10 T FT GS S2046FTGS	DV 12 FT GS 1205FTGS	Video 15 FT GS 1505FTGS	Video 18 FT GS 1811FTGS	Cine 7+7 FT GS 1910FTGS
2 - 8kg 4.4 - 17.6lb	0 - 4kg 0 - 8.8lb	1.5 - 8kg 3.3 - 17.6lb	1.5 - 8kg 3.3 - 17.6lb	1 - 10kg 2.2 - 22lb	1 - 10kg 2 - 22lb	Payload range	4 - 12kg 8.8 - 26.5lb	4 - 12kg 8.8 - 26.5lb	1 - 15kg 2 - 33lb	1 - 17kg 2 - 37lb	2 - 22kg 4 - 48lb	2 - 22kg 4 - 48lb
8 steps	5 steps + 0	10 steps	10 steps	10 steps	10 steps	Counterbalance	10 steps	10 steps	12 steps	12 steps	16 steps + boost button	16 steps + boost button
3 / 3 + 0	3 / 3 + 0	3 / 3 + 0	3 / 3 + 0	5 / 5 + 0	5 / 5 + 0	Drag	5 / 5 + 0	5 / 5 + 0	5 / 5 + 0	7 / 7 + 0	7 / 7 + 0	7 / 7 + 0
104mm / 4.1in	120mm / 4.7in	120mm / 4.7in	60mm / 2.4in	120mm / 4.7	60mm / 2.4in	Balance range	120mm / 4.7in	60mm / 2.4in	70mm / 2.8in	70mm 2.8in	150mm / 5.9in	150mm / 5.9in
Ace Plate	Sideloading S	Sideloading S	Touch & Go S	Sideloading S	Touch & Go S	Camera fitting	Sideloading S	Touch & Go S	Touch & Go	Touch & Go	Touch & Go	Sideloading M
5.5kg / 12.1lb	6.1kg / 13.4lb	6.3kg / 13.9lb	6.4kg / 14.1lb	6.4kg / 14.1lb	6.5kg / 14.3lb	Weight	6.7kg / 14.8lb	6.8kg / 15lb	7.2kg / 15.9lb	7.3kg / 16.1lb	8.2kg / 18.1lb	8.2kg / 18.1lb
41 - 169cm 16.1 - 66.5in	41 - 169cm 16.1 - 66.5in	41 - 169cm 16.1 - 66.5in	41 - 169cm 16.1 - 66.5in	41 - 169cm 16.1 - 66.5in	41 - 169cm 16.1 - 66.5in	Height range in spreaderless mode	41 - 170cm 16.1 - 66.9in	41 - 170cm 16.1 - 66.9in	41 - 170cm 16.1 - 66.9in	41 - 170cm 16.1 - 66.9in	42 - 172cm 16.5 - 67.7in	41 - 170cm 16.1 - 66.9in
57 - 174cm 22.4 - 68.5in	57 - 174cm 22.4 - 68.5in	57 - 174cm 22.4 - 68.5in	57 - 174cm 22.4 - 68.5in	57 - 174cm 22.4 - 68.5in	57 - 174cm 22.4 - 68.5in	Height range with mid-level spreader	60 - 176cm 23.6 - 69.3in	60 - 176cm 23.6 - 69.3in	60 - 176cm 23.6 - 69.3in	60 - 176cm 23.6 - 69.3in	61 - 177cm 24 - 69.7in	60 - 176cm 23.6 - 69.3in



**Mid-level
spreader
Systems**



Vision blue FT VB-FT	Vision blue3 FT MS VB3-FTMS	Vision blue5 FT MS VB5-FTMS	SKU	Vision 8AS FT MS V8AS-FTMS	Vision 10AS FT MS V10AS-FTMS	Vision 100 FT MS VB100-FTMS
2.1 - 5kg 4.6 - 11lb	3 - 6.6kg 6.6 - 14.6lb	5.5 - 12kg 12 - 26.5lb	Payload range	5.5 - 14.0kg 12.1 - 30.9lb	6.5 - 17.0kg 14.3 - 37.5lb	7.0 - 20.0kg 15.4 - 44.1lb
Infinitely adjustable Perfect Balance			Counterbalance	Infinitely adjustable Perfect Balance		
Calibrated infinitely adjustable LF drag system			Drag	Calibrated infinitely adjustable LF drag system. TF drag system for Vision 100		
Slide in	Slide in	Slide in	Camera fitting	Slide in	Slide in	Slide in
5.5kg / 12.1lb	5.8kg / 12.9lb	5.8kg / 12.9lb	Weight	7.2kg / 15.9lb	7.3kg / 16.1lb	7.8kg / 17.1lb
41 - 169cm 16.1 - 66.5in	41 - 169cm 16.1 - 66.5in	41 - 169cm 16.1 - 66.5in	Height range in spreaderless mode	40 - 170cm 15.7 - 66.9in	40 - 170cm 15.7 - 66.9in	39 - 169cm 15.4 - 66.5in
Mid-level spreader notincluded	78 - 173cm 30.7 - 68.1in	78 - 173cm 30.7 - 68.1in	Height range with mid-level spreader	69 - 171cm 27.2 - 67.3in	69 - 171cm 27.2 - 67.3in	68 - 170cm 26.8 - 66.9in



**Ground
spreader
Systems**



Vision blue FT GS VB-FTGS	Vision blue3 FT GS VB3-FTGS	Vision blue5 FT GS VB5-FTGS	SKU	Vision 8AS FT GS V8AS-FTGS	Vision 10AS FT GS V10AS-FTGS	Vision 100 FT GS VB100-FTGS
2.1 - 5kg 4.6 - 11lb	3 - 6.6kg 6.6 - 14.6lb	5.5 - 12kg 12 - 26.5lb	Payload range	5.5 - 14.0kg 12.1 - 30.9lb	6.5 - 17.0kg 14.3 - 37.5lb	7.0 - 20.0kg 15.4 - 44.1lb
Infinitely adjustable Perfect Balance			Counterbalance	Infinitely adjustable Perfect Balance		
Calibrated infinitely adjustable LF drag system			Drag	Calibrated infinitely adjustable LF drag system. TF drag system for Vision 100		
Slide in	Slide in	Slide in	Camera fitting	Slide in	Slide in	Slide in
6.5kg / 14.3lb	6.5kg / 14.3lb	6.5kg / 14.3lb	Weight	7.1kg / 15.7lb	7.2kg / 15.9lb	7.7kg / 17.1lb
41 - 169cm 16.1 - 66.5in	41 - 169cm 16.1 - 66.5in	41 - 169cm 16.1 - 66.5in	Height range in spreaderless mode	40 - 170cm 15.7 - 66.9in	40 - 170cm 15.7 - 66.9in	39 - 169cm 15.4 - 66.5in
54 - 173cm 21.3 - 68.1in	54 - 173cm 21.3 - 68.1in	54 - 173cm 21.3 - 68.1in	Height range with mid-level spreader	59 - 175cm 23.2 - 68.9in	59 - 175cm 23.2 - 68.9in	58 - 174cm 22.8 - 68.5in